





DATASHEET

RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 2m



General data

The unshielded Cat.6 RJ45 patch cable with ensures excellent performance for 5 Gigabit Ethernet applications. The moulded grommet captivates with its **slim design** and thus simplifies the insertion process in cramped conditions.

Cross section 4 x 2 x **AWG24/7**

Moulded grommet, slim design

Length imprint on the boot

Allgemeine Daten

Model	Unshielded
Suitable for degree of protection (IP)	IP20
Fire retardant version	False
Jacket Material	Polyvinylchlorid (PVC)
AWG-size	24/7
Length imprint	True

General data

Locking lever	False
Pin assignment	1:1

This datasheet was created automatically on 08-05-2024 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 2m

Contacts	Gold plated μ " gold plated
Colour outer sheath	yellow
Allocation	acc. TIA/EIA 568B
Colour anti-kink sleeve	yellow
Connector type	RJ45 Standard
Cable type	U/UTP
Area of Application	Industrial Ethernet
Anti-kink sleeve	plugged in
Halogen free	False
Category	6

Mechanical characteristics

Bending radius	30 mm
Mating cycles	750

Cable construction

Conductor Material	CCA
--------------------	-----

Kabelaufbau

Type of connector connection 2	RJ45 8(8)
Type of connector connection 1	RJ45 8(8)
Cable construction	4x2

Cable sheath

Oil resistant (according to EN 60811-404)	False
Silicone-free	True

Kabelmantel

Outer diameter of the cable	5.9 mm
Printing	Cat.6 UTP AWG24 stranded x 4pairs cable www.efb-elektronik.de

Environmental conditions

Temperature range	-20 70 °C
-------------------	-----------

Electrical characteristics

This datasheet was created automatically on 08-05-2024 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 2m

NVP value	- %
POE class	PoE+ acc. to IEEE802.3at
Current Rating	max. 1 A

Elektrische Eigenschaften

Operating-/ tempering voltage	max. 50 V DC
-------------------------------	--------------

Übertragungstechnische Eigenschaften

Bandwidth	250MHz
Transmission	5Gbit

Standards, approvals, certifications

Cabling standard	EN50173
Connector	IEC 60603-7-4
Oil resistant (acc. EN 60811-2-1)	False

Available variants

ArtNr.	Bezeichnung	Length	Längentoleranz
K8100GE.0,25	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 0,25m	0.25 m	± 5 %
K8100GE.0,5	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 0,5m	0.5 m	± 5 %
K8100GE.1	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 1m	1.0 m	± 5 %
K8100GE.1,5	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 1,5m	1.5 m	± 5 %
K8100GE.2	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 2m	2.0 m	± 5 %
K8100GE.3	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 3m	3.0 m	± 5 %
K8100GE.5	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 5m	5.0 m	± 5 %
K8100GE.7,5	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 7,5m	7.5 m	± 5 %
K8100GE.10	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 10m	10.0 m	± 5 %
K8100GE.15	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 15m	15.0 m	± 5 %
K8100GE.20	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 20m	20.0 m	± 5 %
K8100GE.30	RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 30m	30.0 m	± 5 %


Drawings

This datasheet was created automatically on 08-05-2024 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6 U/UTP PVC CCA yellow 2m



This datasheet was created automatically on 08-05-2024 . Technical changes reserved.

