

# LANC/LANS Splice Packs, LC

50 µm multimode (OM4), standard splice cassette, for heat-shrink and crimp splice protectors (violet boots)

CORNING

The LANscape® LANC/LANS splice packs are matched to the LANscape LANC/LANS patch panels which provide up to 48 fibre (24 port) capacity for LC duplex connectivity and 24 fibre (12 port) capacity for SC duplex or ST® Compatible connectivity.

## Features and Benefits

---

---

---

Splice cassettes delivered with covers, with the option of

---

---

Max. 4 cassettes / LANC panel



Part Number: SP12-03Q-S8-V

## Specifications

### General Specifications

Application	
	50 µm MM (OM4)

### Temperature Range

Operation	-20 °C to 60 °C
Installation and Assembly	-5 °C to 50 °C
	-25 °C to 70 °C

### Design - Hardware

Fibre count	12
	12
	1
	2 m
Connector type	LC

CORNING

# LANC/LANS Splice Packs, LC

50 µm multimode (OM4), standard splice cassette, for heat-shrink and crimp splice protectors (violet boots)



## Design - Hardware

	Bundle colour coded to telcordia on primary and secondary
Number of splice trays	1
Splice tray type	
Splice Protectors Type	Heat-shrink

## Mechanical Characteristics

Dimensions (HxWxD)	10 mm x 140 mm x 90 mm

## Optical Specification - Hardware

	0.35 dB
--	---------

Part Number	SP12-03Q-S8-V
Product Description	LANC/LANS Splice Packs, LC, 50 µm multimode (OM4), standard splice cassette, for heat-shrink and crimp splice protectors (violet boots)

	280 mm x 280 mm x 77 mm
Units per delivery	4/1



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

