


DATASHEET

19" Network Cabinet 24U 600x600, IP55, with Pre-Assembled Plinth, RAL7035



General data

19" Network cabinet according to DIN 41494
 Steel sheet housing with welded frame, completely pre-assembled
 Pre-assembled plinth 100 mm
 Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, depth-adjustable in 25 mm raster
 Numbering of rack units at the 19" profiles
 Front and rear door steel, 1-part
 Front and rear door with 3-point locking with turning handle, lockable

 Door opening angle front and rear > 120°
 Side walls not detachable
 Inner roof pre-punched openings for fan units

This datasheet was created automatically on 09-05-2024 . Technical changes reserved.



DATASHEET

19" Network Cabinet 24U 600x600, IP55, with Pre-Assembled Plinth, RAL7035

Bottom prepared with air inlet filters and rubber grommets Ø 80 mm for cable entry
 Internal earthing of all cabinet sections
 Max. load 1000 kg
 Paint finish RAL7035, light grey
 Protection degree IP55
 Included accessories: 1 x set of captive nuts (PU 20 pcs.), pre-installed plinth, 2 x key
 Delivery in transport packaging on disposable pallet

Allgemeine Daten

With socket	True
With front door	True
Type of back door	Steel door 1-part
Type of ventilation	Passive
With backside door	True
Surface finishing	Powder coating
With roof plate	True
Type of front door	Steel door 1-part
With sidewall	True
Mounting level	Front and rear
Model	With permanent frame
With earthing	True

General data

Modular spacing	482.6 mm (19 inch)
Degree of protection	IP55
Material	steel
Demountable	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Number of height units	Width	Höhe	RAL-Nummer	Anzahl der Türen	Geeignete Lüfter
692524IP55.GR	19" Network Cabinet 24U 600x600, IP55, with Pre-Assembled Plinth, RAL7035	grey	600 mm	24 U	600 mm	1360 mm	7035	2	nur 2-fach

This datasheet was created automatically on 09-05-2024 . Technical changes reserved.

