

# DATASHEET

## 19" Network Cabinet 24U 600x600, IP55, with Pre-Assembled Plinth, RAL9005



### General data

19" Network cabinet according to DIN 41494  
 Steel sheet housing with welded frame, completely pre-assembled  
 Pre-assembled plinth 100 mm  
 Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, depth-adjustable in 25 mm raster  
 Numbering of rack units at the 19" profiles  
 Front and rear door steel, 1-part  
 Front and rear door with 3-point locking with turning handle, lockable  
  
 Door opening angle front and rear > 120°  
 Side walls not detachable  
 Inner roof pre-punched openings for fan units

This datasheet was created automatically on 09-05-2024 . Technical changes reserved.



# DATASHEET

## 19" Network Cabinet 24U 600x600, IP55, with Pre-Assembled Plinth, RAL9005

Bottom prepared with air inlet filters and rubber grommets Ø 80 mm for cable entry  
 Internal earthing of all cabinet sections  
 Max. load 1000 kg  
 Paint finish RAL9005, jet black  
 Protection degree IP55  
 Included accessories: 1 x set of captive nuts (PU 20 pcs.), pre-installed plinth, 2 x key  
 Delivery in transport packaging on disposable pallet

### Allgemeine Daten

With socket	True
With front door	True
Type of back door	Steel door 1-part
Type of ventilation	Passive
With backside door	True
Surface finishing	Powder coating
With roof plate	True
Type of front door	Steel door 1-part
With sidewall	True
Mounting level	Front and rear
Model	With permanent frame
With earthing	True

### General data

Modular spacing	482.6 mm (19 inch)
Degree of protection	IP55
Material	steel
Demountable	False

### Available variants

ArtNr.	Bezeichnung	Colour	Depth	Number of height units	Width	Höhe	RAL-Nummer	Anzahl der Türen	Geeignete Lüfter
692524IP55.TS	19" Network Cabinet 24U 600x600, IP55, with Pre-Assembled Plinth, RAL9005	black	600 mm	24 U	600 mm	1360 mm	9005	2	nur 2-fach

This datasheet was created automatically on 09-05-2024 . Technical changes reserved.

