


# DATASHEET

## 19" Network Cabinet 24U 800x800, IP55, with Pre-Assembled Plinth, RAL7035



### General data

- 19" Network cabinet according to DIN 41494
- Steel sheet housing with welded frame, completely pre-assembled
- Pre-assembled plinth 100 mm
- Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, depth-adjustable in 25 mm raster
- Numbering of rack units at the 19" profiles
- Front and rear door steel, 1-part
- Front and rear door with 3-point locking with turning handle, lockable
- Door opening angle front and rear > 120°
- Side walls not detachable
- Inner roof pre-punched openings for fan units

This datasheet was created automatically on 09-05-2024 . Technical changes reserved.



# DATASHEET

## 19" Network Cabinet 24U 800x800, IP55, with Pre-Assembled Plinth, RAL7035

Bottom prepared with air inlet filters and rubber grommets Ø 80 mm for cable entry  
 Internal earthing of all cabinet sections  
 Max. load 1000 kg  
 Paint finish RAL7035, light grey  
 Protection degree IP55  
 Included accessories: 1 x set of captive nuts (PU 20 pcs.), pre-installed plinth, 2 x key  
 Delivery in transport packaging on disposable pallet

### Allgemeine Daten

With socket	True
With front door	True
Type of back door	Steel door 1-part
Type of ventilation	Passive
With backside door	True
Surface finishing	Powder coating
With roof plate	True
Type of front door	Steel door 1-part
With sidewall	True
Mounting level	Front and rear
Model	With permanent frame
With earthing	True

### General data

Modular spacing	482.6 mm (19 inch)
Degree of protection	IP55
Material	steel
Demountable	False

### Available variants

ArtNr.	Bezeichnung	Colour	Depth	Number of height units	Width	Höhe	RAL-Nummer	Anzahl der Türen	Geeignete Lüfter
692724IP55.GR	19" Network Cabinet 24U 800x800, IP55, with Pre-Assembled Plinth, RAL7035	grey	800 mm	24 U	800 mm	1360 mm	7035	2	2/4/6-fach

This datasheet was created automatically on 09-05-2024 . Technical changes reserved.

