

# DATASHEET

19" Wall Housing IP55, 7U, Steel Door, Depth 450 mm, RAL7035



## General data

Steel sheet housing with welded corpus, completely pre-assembled

Right- and left-sided metal covered air inlets for passive ventilation

Side walls not detachable

Roof hinged, inner roof prepared for mounting of Plug&Play fan unit Art.-No. 691656GR (cable not included, please order separately, e.g. Art.-No. EK504.x)

Bottom with PG glands 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC blind grommets

**For depth 450 mm inside 2 x 19" profile rails front-sided, galvanised, with numbering of rack units (U)**

**For depth 600 mm inside 4 x 19" profile rails (2 front, 2 rear), galvanised, with numbering of rack units (U)**

Front door steel sheet with reinforcement and 3-point bar locking, lockable, with profile half-cylinder acc. to DIN 18252 / EN1303

Profile half-cylinder exchangeable by customer

Cabinet parts inside completely earthed

Max. load 100 kg

Paint finish RAL7035, light grey

Protection degree IP55

Plinth for use as standing cabinet available as option

Included accessories: 4 x Wall mount angle, 2 x key

This datasheet was created automatically on 09-05-2024 . Technical changes reserved.



# DATASHEET

## 19" Wall Housing IP55, 7U, Steel Door, Depth 450 mm, RAL7035

### Allgemeine Daten

With front door	True
Type of ventilation	Passive
Surface finishing	powder coating
Number of cartons	1
With roof plate	True
Mounting level	Front side
With sidewall	True
Model	With permanent frame
With earthing	True
Number of doors	1
Type of profile rail	L-shaped

### General data

Modular spacing	482.6 mm (19 inch)
Demountable	True
Degree of protection	IP55
Material	steel

### Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-Nummer
691707IP55.1	19" Wall Housing IP55, 7U, Steel Door, Depth 450 mm, RAL7035	grey	450 mm	450 mm	100 kg	7 U	600 mm	7035
691709IP55.1	19" Wall Housing IP55, 9U, Steel Door, Depth 450 mm, RAL7035	grey	450 mm	540 mm	100 kg	9 U	600 mm	7035
691712IP55.1	19" Wall Housing IP55, 12U, Steel Door, Depth 450 mm, RAL7035	grey	450 mm	670 mm	100 kg	12 U	600 mm	7035

This datasheet was created automatically on 09-05-2024 . Technical changes reserved.

