

LANC/LANS Splice Packs, SC

50 µm multimode (OM3), standard splice cassette, for heat-shrink and crimp splice protectors

CORNING

Splice cassettes delivered with 900 µm TB (Easy Strip) fibres pre-stripped to 250 µm

TB fibres are Telcordia colour-coded on both 900 µm and 250 µm coating layers

Pigtails 2 metre in length: 0.8 metre 900 µm and 1.2 metre 250 µm

crimp splice or heat-shrink organisers

Each cassette holds 12 splices



General Specifications

	Splicing
Fibre category	

Temperature Range

Storage	

Design - Hardware

Number of pigtails	
Number of pigtail bundles	
Pigtail length	

LANC/LANS Splice Packs, SC

50 µm multimode (OM3), standard splice cassette, for heat-shrink and crimp splice protectors



Design - Hardware

Pigtail Type	coating
	standard with organizers for heat-shrink splice protectors

Mechanical Characteristics

Weight	0.7 kg
--------	--------

Optical Specification - Hardware

Pigtail insertion loss	
------------------------	--

Ordering Information

Shipping Information

Packing dimensions (L x W x H)	
Shipping Weight	1 kg



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2015 Corning Optical Communications. All rights reserved.