

UniCam® Connector, ST® Compatible

50 µm multimode (OM2)


CORNING

Corning UniCam® ST connectors offer optical performance in a fast, easy field-termination solution ideal for fibre-to-the-workstation applications where setup and teardown time is critical. The high-precision mechanical splice technology enables fibre optic networks to be installed quickly and cost effectively. Installation of an LC, SC or ST® compatible connector can be accomplished in about 50 seconds to one minute with the UniCam High-Performance Tool Kit.

The lightweight, handheld installation tool and high-performance precision cleaver virtually eliminate human variability during installation, ensuring terminations are right the first time, every time. This kit was designed with consideration for network installers, from the cleaver, with its intuitive, hand-held precision design and dual-clamp precision hold, to the installation tool, with its immediate go/no-go feedback signal indicating proper mating of the field fibre to the fibre stub. Installation is as easy as strip, clean, cleave, cam and crimp, with exceptional optical performance assured. Every UniCam® connector is assured to meet the published specification at the time of installation or Corning will replace it.

Corning UniCam® high-performance connectors offer best-in-class optical performance in a fast, easy field-termination solution. These high-precision zirconia ceramic ferrule connectors assured exceptional insertion loss – 0.1 dB typical/0.5 dB maximum per connector pair for multimode, 0.2 dB typical/0.5 dB maximum per connector pair for single-mode. Installation of an LC, SC or ST® compatible connector can be accomplished in about 50 seconds to one minute with the UniCam high-performance tool kit.

The lightweight, handheld installation tool and high-performance precision cleaver virtually eliminate human variability during installation, ensuring terminations are right the first time, every time. This kit was designed with consideration for network installers, from the cleaver, with its intuitive, hand-held precision design and dual-clamp precision hold, to the installation tool, with its immediate go/no-go feedback signal indicating proper mating of the field fibre to the fibre stub. Installation is as easy as strip, clean, cleave, cam and crimp, with exceptional optical performance assured. Every UniCam® connector is assured to meet the published specification at the time of installation or Corning will replace it.



Features and Benefits

Performance guarantee

100 percent yield guarantee

UniCam[®] Connector, ST[®] Compatible

50 µm multimode (OM2)

CORNING

Features and Benefits

Broad operating temperature (-40° to +75°C)

Utility and flexibility

Factory-polished end face

Consistent optical performance

Fast termination and no consumables

Low installation cost

Minimum insertion loss

Optimum optical performance

Standards

Approvals and Listings Passed EIA/TIA 568-B.3

Intermateability Connectors are FOCIS compliant with TIA/EIA 604-2 and IEC61754-2

Specifications

General Specifications

Product type	Field-Installable Connectors
Technology	No-Epoxy/No-Polish
Keyed	No
Corning Logo	Yes
Packaging	Single Pack
Fibre category	50 µm MM (OM2)

Temperature Range

Operation	-40 °C to 75 °C exceeding EIA/TIA 568-B.3 (-40 °F to 167 °F exceeding EIA/TIA 568-B.3)
-----------	--

Design - Connector

Connector type	ST [®] Compatible
Ferrule Material	Ceramic
Housing material	Composite
Housing colour	Amber

UniCam[®] Connector, ST[®] Compatible

50 µm multimode (OM2)

CORNING

Design - Connector

Boot colour	black
Crimp size	1.6 mm / 2.0 mm / 3.0 mm
Pinned	No
Polish	PC

Mechanical Specifications - Connector

Durability	0.2 dB change by 500 rematings, FOTP-21
Nominal fibre outer diameter	125 µm
Tensile strength jacketed cable	50 N, change 0.2 dB, FOTP-6 (11 lb, change 0.2 dB, FOTP-6)
Tensile strength 900 µm cable	4.9 N, change 0.2 dB, FOTP-6 (1.1 lb, change 0.2 dB, FOTP-6)

Optical Specifications - Connector

Insertion loss, typical	0.1 dB
Insertion Loss, Maximum	0.5 dB
Reflectance	-26 dB

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	95-050-51
Product Description	UniCam [®] High-Performance Connector, ST [®] Compatible, 50 µm multimode (OM2), ceramic ferrule, logo, single pack, amber housing, black boot
EAN Code	4042673249382

Shipping Information

Units per delivery	1/1
Package Contents	Connector, crimp band, boot (900 µm), boot (3.0 mm)

UniCam[®] Connector, ST[®] Compatible

50 µm multimode (OM2)

The logo consists of a solid blue square with the word "CORNING" written in white, uppercase, sans-serif font in the center.

Notes



**Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea**

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2015 Corning Optical Communications. All rights reserved.