

Everon® Copper Datacom F/UTP 300/24, Outdoor, Category 5e, PE, Fca 4P, Black

CORNING

Part Number:
CCXDAE-C0047-C001-L7

The Everon® Copper Datacom F/UTP 300/24 cable is designed up to 300MHz and its transmission characteristics exceed Category 5e specifications according to EN50288-2-1 IEC 61156-5. High system margins for the complete link according to the last version of ISO/IEC 11801 and EN 50173 (Series) will be achieved by using corresponding hardware together with this highend copper cable. Due to the very low delay skew between the pairs these FutureCom cables are especially suitable for Gigabit Ethernet according to IEEE 802.3an. The cable has a streamlined construction and low weight. Overall shielding with with a Allaminated foil and each twisted pair unshielded (F/UTP). The cable satisfies Class B interference radiation standards according to EN 55022, as well as immunity according to EN 55024, which enables the realization of CE-compatible networks.

Features and Benefits

F/UTP 300/24 cable designed up to 300 MHz

Fulfils all requirements of category 5e EN50288-2-1 and IEC 61156-5

Suitable for Classe D to Da according to ISO/IEC 11801. EN50173 and 1 Gigabit Ethernet according to IEEE 802.3an


Tested and approved for Power over Ethernet applications (PoE/PoE+/4PPoE) according to IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt up to 90W

PE Outdoor jacket Low smoke and halogen-free (LSZH)

Overall shielding with with a Allaminated foil and each twisted pair unshielded (F/UTP)

Length marking on jacket

Fca



Everon® Copper Datacom F/UTP 300/24, Outdoor, Category 5e, PE, Fca, 4P, Black

Everon® Copper Datacom F/UTP 300/24, Outdoor, Category 5e, PE, Fca 4P, Black

CORNING

Specifications

General Specifications

Environment	Outdoor
Category	5E
Cable type	F/UTP
Halogen-free	Yes
Radial watertight	Yes
Construction	Simplex, 4P
UV resistant	Yes
Reaction to Fire	Fca
Legacy Part Number	CCXDAE-C0047-C001-L7
Brand	Everon

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 61156-5, EN 50288-2-1, ISO/IEC 11801 Ed. 2.2, EN 50173-1, ANSI/TIA-568-C.2, IEC 60304
Design And Test Criteria	1000 Base-T IEEE 802.3 an; PoE / PoE++ IEEE 802.3af, IEEE 802.3at
Smoke density	IEC 61034-2

Environmental Conditions

Halogen-free	Yes
Temperature range, installation	0 °C to 50 °C
Temperature range, operation	-40 °C to 60 °C

Cable Design

Conductor	Copper Wire, AWG 24/1
Conductor insulation	Solid PE

Everon® Copper Datacom F/UTP 300/24, Outdoor, Category 5e, PE, Fca 4P, Black

CORNING

Cable Design

Twisting	2 cores to a pair
Outer jacket material	PE

Mechanical Characteristics

Fire load	390 MJ/km
Nominal outer diameter	6.2 mm
Min. bend radius installation	8x Cable-Ø
Min. bend radius operation	3x Cable-Ø (over flat side)
Maximum tensile strength	93 N

Electrical Characteristics

Conductor resistance unbalance	2 %
Delay skew	45 ns/100 m
Max. loop resistance	190 Ω/km
Propagation delay	545 ns/100 m
Voltage rating	Less than 75 V DC max and less than 50 V ACC max
Propagation velocity at >10 MHz (NVP*c)	69 %
Coupling attenuation	55 dB
Segregation Class	d
Insulation Resistance	> 5000 MΩ*km

Dimensions

Weight	36 kg
--------	-------

Ordering Information

Product Number	CCXDAE-C0047-C001-L7
Cable length	1000 m

Everon® Copper Datacom F/UTP 300/24, Outdoor, Category 5e, PE, Fca 4P, Black

CORNING

Ordering Information

Packaging method	Drum
Units per delivery	1/1

Electrical Characteristics

Frequency [MHz]	4	10	20	63	100	155	200
Attenuation according to Standard [db/100m]	4.1	6.5	9.3	17.0	22.0		
Typical attenuation [db/100m]	3.8	6.0	8.5	15.2	19.5	25.0	28.0
NEXT according to Standard [db/100m]	56.3	50.3	45.8	38.4	35.3		
Typical NEXT Values [db/100m]	63.0	57.0	52.0	45.0	42.0	39.0	37.0
ACR-N according to Standard [db/100m]	56.3	50.3	45.8	38.4	35.3		
Typical ACR-N Values [db/100m]	59.2	51.0	43.5	29.0	22.5	14.0	9.0



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
00 800 2676 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.