

FutureCom™ Cat. 3 / ISDN Patch Panel 19", 1U, 50 Ports FutureCom™ Cat. 3 / ISDN Patch Panel 19", 1U, 50 Ports

CORNING

Part Number: **CAXCSV-05000-C001**

The FutureCom™ Cat.3 / ISDN telephone patch panel offers a simple and economical way to connect the telephone system or the telephone backbone with the structured wiring. The telephone connection can be made by one or two pairs (analogue and ISDN technology)

Features and Benefits

19" patch panel, 1U with 50 unshielded 8-pin RJ45 jacks

Wire connection via 4-pin LSA/110 connect dual cutting clamps for AWG 22-26

Wiring according to ISO/IEC 11801 Ed.2.2/ EN 50173-1,

configuration: Pin 3/6 and Pin 4/5

Grounding via M6 screw with nut and lock washer in the patch panel

Shield connection directly on the circuit board

Integrated cable strain relief

FutureCom™ Cat. 3 / ISDN Patch Panel 19", 1U, 50 Ports FutureCom™ Cat. 3 / ISDN Patch Panel 19", 1U, 50 Ports

CORNING

Specifications

Environmental Conditions

Environmental Compatibility	Recyclable
Temperature Range, Installation	-40 °C - 70 °C (-40 °F - 158 °F)
Temperature Range, Operation	-10 °C - 60 °C (14 °F - 140 °F)

Design

Housing Material	High-grade steel
Height Unit	1 U
Color	High-grade steel
Number of Ports	50

Mechanical Specifications

Housing Material	High-grade steel
------------------	------------------

General Specifications

Category	3
----------	---

Dimensions

Height	120 mm
Width	44 mm
Depth	483 mm

FutureCom™ Cat. 3 / ISDN Patch Panel 19", 1U, 50 Ports FutureCom™ Cat. 3 / ISDN Patch Panel 19", 1U, 50 Ports

CORNING

Ordering Information

Units per Delivery

1/1

Standards

RoHS Free of hazardous substances according to RoHS 2011/65/EU



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea