

SST-Drop™ Single-Tube, Dielectric, Gel-Filled Cable 2 F, E9/125 SMF-28® ULTRA

CORNING

Part Number:
002ZB4-13120A20

Corning SST -Drop™ dielectric cables offer the ease of installation of standard ALTOS® cables in an easy -access, single -tube design. The dielectric version eliminates any bonding and grounding requirements. Dielectric cables are also available in preconnectorized assemblies.

Features and Benefits

Dielectric design


Eliminates bonding

Standard ALTOS® Cable tube design in single-tube design

Standard practices and hardware compatibility

Crush resistance

Fiber protection and signal integrity



SST-Drop™ Single-Tube, Dielectric, Gel-Filled Cable 2 F, E9/125 SMF-28® ULTRA

CORNING

Specifications

General Specifications

Cable Type	Single Tube
Environment	Outdoor
Product Type	Self-Supporting, Figure-8
Fiber Category	SMF-28® Ultra
Application	Aerial, Duct, Drop
Cable geometry	Other

Standards

Reaction to Fire	Fca
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-22 Method F5B
Level of corrosion	Non-corrosive according to IEC 60754-2

Environmental Conditions

Temperature Range, Installation	-30 °C to 70 °C (-22 °F to 158 °F)
Temperature Range, Operation	-40 °C to 70 °C (-40 °F to 158 °F)
Temperature Range, Storage	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design

Cable Marking	Metre - CORNING -Month/Year - Handset - 2E9ULTRA - ID Number
Central Element	Dielectric
Fiber Count	2
Outer Jacket Color	Black
Outer Jacket Material	Polyethylene (PE)
Buffer Tube Diameter	3 mm

SST-Drop™ Single-Tube, Dielectric, Gel-Filled Cable 2 F, E9/125 SMF-28® ULTRA

CORNING

Cable Design

Cable Marking Color	White
Fiber Coloring	Blue, Orange
Fibers per Tube	2
Color Code Standards	Telcordia

Mechanical Specifications

Crush Resistance	3000 N/10 cm
Max. Tensile Strength, Long-Term	400 N
Max. Tensile Strength, Short-Term	1350 N
Min. Bend Radius Operation	80 mm
Nominal Outer Diameter	8.1 mmx 4.5 mm

Optical Characteristics

Fiber Code	Z
Performance Option Code	20
Fiber Category	OS2
Fiber Type	Single-mode (OS2) / 250 µm
Fiber Name	Bend-Improved Single-mode (OS2)
Maximum Attenuation	0.34 dB/km / 0.34 dB/km / 0.20 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Compliance	ITU-T G.652.D and ITU-T G.657.A1
Fiber Core Diameter	8.2 µm
Cladding diameter	125 µm
Coating diameter	242 µm
Dispersion @ 1550 nm	≤ 18 [ps/(nm*km)]
Dispersion @ 1625 nm	≤ 22 [ps/(nm*km)]
Cable cutoff wavelength	1260 nm
Mode-Field Diameter at 1310 nm	9.2 µm

SST-Drop™ Single-Tube, Dielectric, Gel-Filled Cable 2 F, E9/125 SMF-28® ULTRA

CORNING

Optical Characteristics

Mode-Field Diameter at 1550 nm	10.4 μm
PMD Link Design Value	$\leq 0.04 \text{ ps}/(\text{nm}\cdot\text{km})$
PMD maximum individual fiber	$\leq 0.1 \text{ ps}/(\text{nm}\cdot\text{km})$

Dimensions

Cable Weight	30 kg/km
--------------	----------



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.