

ALTOS® Loose Tube Dielectric Armor Outdoor Cable LT 2.3 4x6 E9 SMF-28e+® ITU G652.D

CORNING

Part Number:
024ERG-63122A20

Corning glass-yarn armored loose tube cables are designed for outdoor use for campus, city and intercity backbones in duct installations.

The loose tube cable construction, by isolating the fibers from installations and environmental rigors, provides stable and highly reliable transmission parameters. The buffer tubes and fibers in each tube are color coded for quick and easy identification.

The SZ-stranded construction further reduces installation and environmental influences on the transmission parameters and allows mid-span access.

These cables are designed for installation in conduits and ducts.

Features and Benefits

Waterblocking technology

Outside Plant (OSP) applications

All-dielectric construction

Requires no grounding or bonding

UV and microbe resistant

Can be installed in ducts

Dry cable core by means of water-swellable tape and elements

Allows efficient and craft-friendly cable preparation in outdoor or indoor/outdoor applications

Laminated glass yarns

Improved rodent resistance

Fibres/buffer tubes colour coded to Telcordia-Bellcore

Easy identification of the individual tubes and fibres

SZ-stranded, loose tube design

Isolates fibers from installation and environmental rigors and facilitates mid-span access



ALTOS® Loose Tube Dielectric Armor Outdoor Cable LT 2.3 4x6 E9 SMF-28e+® ITU G652.D

CORNING

Specifications

General Specifications

Cable Type	Loose Tube
Environment	Outdoor
Product Type	Dielectric armor
Fiber Category	Single-mode (OS2)
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	A-DQ(ZN)B2Y
Application	Duct
Cable geometry	Round

Standards

Fiber Standards	TIA/EIA-492CAAB, IEC 60793-2-50 Type B1.3, ITU-T G.652.D, ISO/IEC 11801 Ed.2.2
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-2 F5

Environmental Conditions

Temperature Range, Installation	-5 °C to 50 °C
Temperature Range, Operation	-30 °C to 70 °C
Temperature Range, Storage	-40 °C to 70 °C

Cable Design

Cable Marking	Meter - Handset - Sine - CORNING - Year -ALTOS (R) A-DQ(ZN)B2Y 4X6 E9 LT 2.3
Central Element	Dielectric
Fiber Count	24
Number of Ripcords	1
Outer Jacket Color	Black
Outer Jacket Material	Linear Low Density Polyethylene (LLDPE)

ALTOS® Loose Tube Dielectric Armor Outdoor Cable LT 2.3 4x6 E9 SMF-28e+® ITU G652.D

CORNING

Cable Design

Outer Jacket Nominal Thickness	1.5 mm
Tensile Strength Elements and/or Armoring - Layer 1	Laminated glass yarn armor
Buffer Tube Color	Blue, Orange, Green, Brown
Buffer Tube Diameter	2.25 mm
Central Element Diameter	2.5 mm
Filling Element Color	Natural
Number of Active Tubes	4
Number of Filling Elements	2
Number of Tube Positions	6
Tape	Water-swellable
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White
Fibers per Tube	6
Color Code Standards	Telcordia

Mechanical Specifications

Crush Resistance	2000 N/10 cm
Max. Tensile Strength for Installation	4000 N
Min. Bend Radius Installation	215 mm
Min. Bend Radius Operation	160 mm
Nominal Outer Diameter	10.9 mm

Optical Characteristics

Cable cutoff wavelength	1260 nm
Fiber Code	E
Fiber Name	Single-mode (OS2)
Fiber Type	Single-mode (OS2) / 250 µm
Fiber Compliance	ITU-T G.652.D
Performance Option Code	22

ALTOS® Loose Tube Dielectric Armor Outdoor Cable LT 2.3 4x6 E9 SMF-28e+® ITU G652.D

CORNING

Optical Characteristics	
Fiber Core Diameter	8.2 µm
Cladding diameter	125 µm
Maximum Attenuation	0.36 dB/km / 0.36 dB/km / 0.22 dB/km
Mode-Field Diameter at 1310 nm	9.2 µm
Mode-Field Diameter at 1550 nm	10.4 µm
Wavelengths	1310 nm / 1383 nm / 1550 nm
PMD Link Design Value	≤ 0.06 ps/(nm*km)
PMD maximum individual fiber	≤ 0.1 ps/(nm*km)
Coating diameter	242 µm
Fiber Category	OS2
Dispersion @ 1550 nm	≤ 18 [ps/(nm*km)]
Dispersion @ 1625 nm	≤ 22 [ps/(nm*km)]

Dimensions	
Cable Weight	92 kg/km
Max. cable length per reel/drum	6000 m



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.