

Loose Tube Dielectric Armor Indoor/Outdoor Cable 8x12 E9 SMF-28e+® ITU G652.D LT 2.3

CORNING

Part Number:
096ERU-T3122A2G

Corning® MPC (multipurpose cable) stranded loose tube cables are flame-retardant, indoor/outdoor cables designed for interbuilding and intrabuilding backbones in duct and riser applications.

The loose tube cable construction, by isolating the fibers from installations and environmental rigors, provides stable and highly reliable transmission parameters. The buffer tubes and fibers in each tube are color coded for quick and easy identification.

The SZ-stranded construction further reduces installation and environmental influences on the transmission parameters and allows mid-span access. These cables are designed for installation in conduits, ducts and in-house.

Features and Benefits

All-dielectric construction

Requires no grounding or bonding

UV- and microbe-resistant

Can be installed in ducts or conduits

Waterblocking technology

OSP (outdoor) applications

Laminated glass yarns

Improved rodent resistance

Fibres/buffer tubes colour coded to Telcordia-Bellcore

Easy identification of the individual tubes and fibres

Silicon-free outer jacket

The cable jacket is free of harmful to paint structures

Flame retardant

LSZH/FRNC



Loose Tube Dielectric Armor Indoor/Outdoor Cable 8x12 E9 SMF-28e+® ITU G652.D LT 2.3, Eca

Loose Tube Dielectric Armor Indoor/Outdoor Cable 8x12 E9 SMF-28e+® ITU G652.D LT 2.3

CORNING

Specifications

General Specifications

Cable Type	Loose Tube
Environment	Indoor/Outdoor
Product Type	Dielectric armor
Fiber Category	Single-mode (OS2)
Flame Rating	LSZH/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)BH
Application	Duct, General purpose, Horizontal, Vertical Riser
Cable geometry	Round

Standards

Fiber Standards	TIA/EIA-492CAAB, IEC 60793-2-50 Type B1.3, ITU-T G.652.D, ISO/IEC 11801 Ed.2.2
-----------------	--

Standards

Fiber Standards	TIA/EIA-492CAAB, IEC 60793-2-50 Type B1.3, ITU-T G.652.D, ISO/IEC 11801 Ed.2.2
Reaction to Fire	Eca
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-22 Method F5B
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable)
Reaction to Fire Requirements	Reaction to fire according to EN 50575 and EN 13501-6
Smoke density	Low smoke according to IEC 61034
Halogen content test	Zero Halogen according to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Environmental Conditions

Temperature Range, Installation	-5 °C to 50 °C (23 °F to 122 °F)
---------------------------------	-----------------------------------

Loose Tube Dielectric Armor Indoor/Outdoor Cable 8x12 E9 SMF-28e+® ITU G652.D LT 2.3

CORNING

Environmental Conditions

Temperature Range, Operation	-40 °C to 70 °C (-40 °F to 158 °F)
Temperature Range, Storage	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design

Cable Marking	Meter - Handset - CE 17 EN 50575 Eca - Sine - CORNING - Fiber Optic Cable - Year - U-DQ(ZN)BH 96 E9 LT 2.3 LSZH(TM)/FRNC
Central Element	Dielectric with FRNC/LSZH coating
Fiber Count	96
Number of Ripcords	1
Outer Jacket Color	Black
Outer Jacket Material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer Jacket Nominal Thickness	1.5 mm
Buffer Tube Color	Blue, Orange, Green, Brown, Slate, White, Red, Black
Buffer Tube Diameter	2.25 mm
Central Element Diameter	2.8 mm
Fibers per Bundle	12
Number of Active Tubes	8
Number of Tube Positions	8
Tape	Water-swellaable
Tensile Strength Elements and/or Armoring	Laminated glass yarn armor
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Color Code Standards	Telcordia

Mechanical Specifications

Crush Resistance	2000 N/10 cm
Max. Tensile Strength for Installation	4000 N

Loose Tube Dielectric Armor Indoor/Outdoor Cable 8x12 E9 SMF-28e+® ITU G652.D LT 2.3

CORNING

Mechanical Specifications

Min. Bend Radius Installation	245 mm
Min. Bend Radius Operation	185 mm
Nominal Outer Diameter	12.3 mm

Optical Characteristics

Cable cutoff wavelength	1260 nm
Fiber Code	E
Fiber Name	E9/125 SMF28e+®
Fiber Type	Single-mode
Performance Option Code	22
Fiber Core Diameter	8.2 µm
Maximum Attenuation	0.36 dB/km / 0.36 dB/km / 0.22 dB/km
Serial 1 Gigabit Ethernet	5000 MHz*km / - / -
Serial 10 Gigabit Ethernet	10000 MHz*km / - / 40000 MHz*km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Category	OS2

Dimensions

Cable Weight	144 kg/km
Max. cable length per reel/drum	6000 m



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.