

Loose Tube Dielectric Armour Indoor/Outdoor Cable 4x12 G50 MMF ClearCurve® OM2 LT 2.3

CORNING

Part Number: 048TRU-T3138A2G

Corning® MPC (multipurpose cable) stranded loose tube cables are flame-retardant, indoor/outdoor cables designed for interbuilding and intrabuilding backbones in duct and riser applications.

The loose tube cable construction, by isolating the fibers from installations and environmental rigors, provides stable and highly reliable transmission parameters. The buffer tubes and fibers in each tube are color coded for quick and easy identification.

The SZ-stranded construction further reduces installation and environmental influences on the transmission parameters and allows mid-span access. These cables are designed for installation in conduits, ducts and in-house.

Features and Benefits

All-dielectric cable construction

Requires no grounding or bonding

UV- and microbe-resistant

Can be installed in ducts or conduits

Waterblocking technology

OSP (outdoor) applications

Laminated glass yarns

For improved rodent resistance

Fibres/buffer tubes colour coded to Telcordia-Bellcore

Easy identification of the individual tubes and fibres

Silicon-free outer jacket

The cable jacket is free of harmful to paint structures

Flame retardant

LSZH/FRNC



Loose Tube Dielectric Armour Indoor/Outdoor Cable 4x12 G50 MMF
ClearCurve® OM2 LT 2.3, Eca

Loose Tube Dielectric Armour Indoor/Outdoor Cable 4x12 G50 MMF ClearCurve® OM2 LT 2.3

CORNING

Specifications

General Specifications

Cable type	Loose tube
Environment	Indoor/Outdoor
Product type	Dielectric armour
Fibre category	50 µm MM (OM2)
Flame rating	LSZH/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)BH
Application	Duct, General purpose, Horizontal, Vertical Riser
Cable geometry	Round

Standards

Reaction to Fire	Eca
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-22 Method F5B
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable)
Reaction to Fire Requirements	Reaction to fire according to EN 50575 and EN 13501-6
Smoke density	Low Smoke to IEC 61034
Halogen content test	Zero Halogen according to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Environmental Conditions

Temperature range, installation	-5 °C to 50 °C
Temperature range, operation	-40 °C to 70 °C
Temperature range, storage	-40 °C to 70 °C

Loose Tube Dielectric Armour Indoor/Outdoor Cable 4x12 G50 MMF ClearCurve® OM2 LT 2.3

CORNING

Cable Design	
Cable marking	Metre - Handset - CE 17 EN 50575 Eca - Sine - CORNING - Fiber Optic Cable - Year - U-DQ(ZN)BH 48 OM2CC LT 2.3 LSZH(TM)/FRNC
Central element	Dielectric
Fibre count	48
Number of ripcords	1
Outer jacket colour	Black
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer jacket nominal thickness	1.5 mm
Buffer tube colour	Blue, orange, green, brown
Buffer tube diameter	2.25 mm
Central element diameter	2.5 mm
Fibres per bundle	12
Number of active tubes	4
Number of filling elements	2
Number of tube positions	6
Tape	Water-swellaable
Tensile strength elements and/or armouring	Laminated glass yarn armour
Fibre colouring	Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink, turquoise
Fibres per tube	12
Colour Code Standards	Telcordia

Mechanical Specifications	
Crush resistance	2000 N/10 cm
Max. tensile strength for installation	4000 N
Min. bend radius installation	215 mm
Min. bend radius operation	160 mm
Nominal outer diameter	10.9 mm

Loose Tube Dielectric Armour Indoor/Outdoor Cable 4x12 G50 MMF ClearCurve® OM2 LT 2.3

CORNING

Optical Characteristics

Fibre code	T
Performance option code	38
Fibre category	OM2
Fibre Type	Multimode
Fibre name	50 µm MM (OM2)
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fibre compliance	IEC 60793-2-10
Fibre core diameter	50 µm
Cladding diameter	125 µm
Coating diameter	242 µm
Serial 1 gigabit ethernet	750 m / 600 m
Serial 10 gigabit ethernet	150 m / -
Minimum effective modal bandwidth (EMB)	950 MHz*km / -
Min. overfilled launch (OFL) bandwidth	700 MHz*km / 500 MHz*km

Dimensions

Cable Weight	117 kg/km
Max. cable length per reel/drum	4000 m



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.