

Central Tube Dielectric Armor Indoor/Outdoor Cable 1x8 G50 MMF ClearCurve® OM3 CT 3.0

CORNING

Part Number:
008TEU-13188A2G

The central tube cable construction, by isolating the fibers from installations and environmental rigors, provides stable and highly reliable transmission parameters. The fibers in are color coded for quick, easy identification. Based on a central buffer tube cable construction, is very compact, light and flexible, and ideal for connections requiring a moderate fiber count. These cables are designed for installation in conduits, ducts and in-house.

Features and Benefits

All-dielectric construction

Requires no grounding or bonding

Laminated swelling glass yarns

Improved rodent resistance and longitudinal water protection

UV- and microbe-resistant

Can be installed in ducts or conduits

Small diameter and bend radius

Easy installation in space-constrained areas

Fibers color coding to Telcordia-Bellcore

Easy identification of the individual fibers

Waterblocking technology



OSP (outdoor) applications

Silicon-free outer jacket

The cable jacket is free of harmful to paint structures

Flame retardant

LSZH/FRNC



Central Tube Dielectric Armor Indoor/Outdoor Cable 1x8 G50 MMF ClearCurve® OM3 CT 3.0

CORNING

Specifications

General Specifications

Cable Type	Single Tube
Environment	Indoor/Outdoor
Product Type	Dielectric armor
Fiber Category	50 µm MM (OM3)
Flame Rating	LSZH/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)BH
Application	Duct, General purpose, Horizontal, Vertical Riser
Cable geometry	Round

Standards

Reaction to Fire	Dca, s2, d2, a1
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-22 Method F5B
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable) and IEC 60332-3-24 (bunch of cables)
Reaction to Fire Requirements	Reaction to fire according to EN 50575 and EN 13501-6
Smoke density	Low smoke according to IEC 61034
Halogen content test	Zero Halogen according to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Environmental Conditions

Temperature Range, Installation	-5 °C to 50 °C (23 °F to 122 °F)
Temperature Range, Operation	-20 °C to 60 °C (-4 °F to 140 °F)
Temperature Range, Storage	-25 °C to 70 °C (-13 °F to 158 °F)

Central Tube Dielectric Armor Indoor/Outdoor Cable 1x8 G50 MMF ClearCurve® OM3 CT 3.0

CORNING

Cable Design

Cable Marking	Meter - Handset - CE 17 EN 50575 Dca,s2,d2,a1 - Sine - CORNING - Fiber Optic Cable - Year - U-DQ(ZN)BH 8 OM3CC CT 3.0 LSZH(TM)/FRNC
Fiber Count	8
Number of Ripcords	1
Outer Jacket Color	Black
Outer Jacket Material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer Jacket Nominal Thickness	1.2 mm
Tensile Strength Elements and/or Armoring - Layer 1	Laminated swelling glass yarn armor
Buffer Tube Diameter	3 mm
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black
Fibers per Tube	8

Mechanical Specifications

Crush Resistance	1500 N/10 cm
Max. Tensile Strength for Installation	1000 N
Min. Bend Radius Installation	130 mm
Min. Bend Radius Operation	100 mm
Nominal Outer Diameter	6.6 mm

Dimensions

Cable Weight	46 kg/km
Max. cable length per reel/drum	4000 m



Corning Comunicacoes Opticas • Estrada do Camorim 633 • Jacarepagua CEP 22780-070 • Rio De Janeiro, RJ Brazil
+55 21 3416 5150 • FAX: +55 21 2441 2037 • www.corning.com/opcomm/csa

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.