

Central Tube Steel Armour Indoor/Outdoor DTC Cable

1x24 G50 MMF ClearCurve® OM4 CT 5.0

CORNING

Corning MPC (multi-purpose cable) central tube cables with corrugated steel armoring are flame-retardant, indoor/outdoor cables designed for interbuilding and intrabuilding backbones in duct, direct burial and riser applications.

The central tube cable construction, by isolating the fibres from installations and environmental rigors, provides stable and highly reliable transmission parameters. The fibres are colour coded for quick, easy identification.

The cable construction, based on a central buffer tube, is very compact, light and flexible, and ideal for connections requiring a moderate fiber count.

These cables are designed for installation in conduits, ducts, direct burial and in-house.

Features and Benefits

Waterblocking technology

OSP (outdoor) applications

UV- and microbe-resistant

Can be installed in ducts or conduits

Corrugated steel armoring

Rodent, mechanical protection and direct buried applications

Small diameter and bend radius


Easy installation in space-constrained areas

Fibres colour coding to Telcordia-Bellcore

Easy identification of the individual fibres

Flame retardant

LSZH™/FRNC



Standards

Flame Test Method

Flame retardant to IEC 60332-1-2 (single cable)

Reaction to fire according to EN 50575 and EN 13501-6

Low Smoke to IEC 61034 and Zero Halogen to IEC 60754-1

Non Corrosive to IEC 60754-2

Central Tube Steel Armour Indoor/Outdoor DTC Cable

1x24 G50 MMF ClearCurve® OM4 CT 5.0

CORNING

Standards

Waterblocking IEC 60794-1-2 F5

Specifications

General Specifications	
Environment	Indoor/Outdoor Universal Cable
Application	Direct Buried, Duct, Vertical Riser, General Purpose Horizontal
Cable type	Central Tube
Product type	Corrugated steel armour
Flame rating	LSZH™/FRNC
Fibre Category	50 µm MM (OM4)
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)(SR)H
Previous part number	FWCT01-S0024-K004-DTC
Previous coding following DIN VDE 0888-3	A-DQ(ZN)(SR)H
Reaction to fire	Eca

Temperature Range	
Installation and assembly	-5 °C to 50 °C
Operation	-30 °C to 75 °C
Storage	-40 °C to 75 °C stored on drum with original packing

Cable Design	
Fibre count	24
Fibre colouring	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Turquoise
Buffer tube colour	Yellow
Buffer tube diameter	3 mm
Buffer tube water blocking	Thixotropic gel
Tensile Strength Elements and/or Armouring - Layer 1	Aramid yarn with swellable elements
Number of ripcords	2
Tensile strength elements and/or armouring - Layer 2	Corrugated steel tape armour with water-swellaable tape
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer jacket colour	Black

Central Tube Steel Armour Indoor/Outdoor DTC Cable

1x24 G50 MMF ClearCurve® OM4 CT 5.0

CORNING

Cable Design

Outer jacket nominal thickness	1.5 mm
Cable marking	Metre - Handset - CE 17 EN 50575 Eca - Sine - CORNING - Fibre Optic Cable - Year - U-DQ(ZN)(SR)H 24 OM4CC CT 5.0 LSZH(TM)/FRNC

Mechanical Characteristics Cable

Nominal Outer Diameter	7.5 mm
Weight	76 kg/km
Min. Bend Radius Installation	150 mm
Min. Bend Radius Operation	110 mm
Max. tensile strength for installation	1000 N
Crush resistance (reversible)	2000 N/10 cm
Fire Load	1.16 MJ/m

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fibre Specifications

Optical Characteristics (cabled)

Fibre name	G50/125 ULTRA-BEND 7.5
Fibre code	T
Fibre core diameter	50 µm
Fibre Category	OM4
Wavelengths	850 nm / 1300 nm
Maximum attenuation	2.8 dB/km / 1.0 dB/km
Typical attenuation	2.4 dB/km / 0.8 dB/km
Serial 1 gigabit ethernet	1100 m / 600 m
Serial 10 gigabit ethernet	550 m / -
Min. overfilled launch (OFL) bandwidth	3500 MHz*km / 500 MHz*km
Minimum effective modal bandwidth (EMB)	4700 MHz*km / -
Induced attenuation @ 7.5 mm radius	< 0.2 dB / -

- Notes:
- 1) Meets 0.75 ns optical skew when used in all Corning Plug and Play™/EDGE™ systems solutions.
 - 2) 50 µm multimode fibre macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel
 - 3) Improved attenuation and bandwidth options available
 - 4) Bend-insensitive single-mode fibres available on request.
 - 5) Contact a Corning Customer Care Representative for additional information

Central Tube Steel Armour Indoor/Outdoor DTC Cable

1x24 G50 MMF ClearCurve® OM4 CT 5.0

CORNING

Ordering Information

Part Number	024TEY-13198H2G
Product Description	Central Tube Steel Armour Indoor/Outdoor DTC Cable 1x24 G50 MMF ClearCurve® OM4 CT 5.0, Eca
EAN Code	4056418782522

Shipping Information

Maximum delivery length	4,000 m
-------------------------	---------



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2017 Corning Optical Communications. All rights reserved.