

MIC® Tight Buffer Indoor Cable 8F G50 MMF ClearCurve® OM3 0.9mm TB3, Dca-s1a, d1, a1

CORNING

Part Number:
008T8Z-32188E2G

Corning® LANscape® indoor cables can be deployed indoor as building backbone (riser) cabling as well as for the cabling between floor distributors. The tight-buffered construction facilitates easier termination for low-fiber-count applications in the local area network (LAN) and eliminates need for fan-out kits.

Features and Benefits

All-dielectric construction

Requires no grounding or bonding

Small diameter and bend radius

Easy installation in space-constrained areas

TB3 tight buffered construction



Easy and consistent stripping over 10 cm

Silicon-free outer jacket

The cable jacket and the outer jacket of subunits (not valid for 900 µm tight buffers) are free of harmful components to paint structures

Flame retardant

LSZH/FRNC



MIC® Tight Buffer Indoor Cable 8F G50 MMF ClearCurve® OM3 0.9mm TB3, Dca-s1a, d1, a1

CORNING

Specifications

General Specifications

Cable Type	Tight-Buffered
Environment	Indoor
Product Type	Dielectric
Fiber Category	50 µm MM (OM3)
Flame Rating	LSZH/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	J-V(ZN)H
Application	General purpose, Horizontal, Vertical Riser
Cable geometry	Round

Standards

Reaction to Fire	Dca, s1a, d1, a1
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable) and IEC 60332-3-24 (bunch of cables)
Reaction to Fire Requirements	Reaction to fire according to EN 50575 and EN 13501-6
Smoke density	Low smoke according to IEC 61034
Halogen content test	Zero Halogen according to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Environmental Conditions

Temperature Range, Installation	-5 °C to 50 °C (23 °F to 122 °F)
Temperature Range, Operation	-20 °C to 60 °C (-4 °F to 140 °F)
Temperature Range, Storage	-25 °C to 70 °C (-13 °F to 158 °F)

MIC® Tight Buffer Indoor Cable 8F G50 MMF ClearCurve® OM3 0.9mm TB3, Dca-s1a, d1, a1

CORNING

Cable Design

Cable Marking	Meter - Handset - CE 23 EN 50575 Dca-s1a,d1,a1 - Sine - CORNING - Fiber Optic Cable - Year - MIC(R) J-V(ZN)H 8 OM3CC TB3 0.9 LSZH(TM)/FRNC
Central Element	Yarn
Fiber Count	8
Number of Ripcords	1
Outer Jacket Color	Aqua
Buffering Diameter	900 µm
Outer Jacket Material	Flame-retardant, non-corrosive/low-smoke, silicon-free, zero-halogen (FRNC/LSZH) material
Outer Jacket Nominal Thickness	0.8 mm
Tensile Strength Elements and/or Armoring - Layer 1	Aramid Yarn
Tight Buffer Color	Blue, Orange, Green, Brown, Slate, White, Red, Black
Tight Buffer Type	TB3 (easy strip up to 10 cm)
Flame Rating	LSZH/FRNC

Mechanical Specifications

Crush Resistance	1000 N/10 cm
Fire Load	0.56 MJ/m
Max. Tensile Strength for Installation	800 N
Min. Bend Radius Installation	83 mm
Min. Bend Radius Operation	55 mm
Nominal Outer Diameter	5.5 mm

Dimensions

Cable Weight	29 kg/km
Max. cable length per reel/drum	4000 m

MIC® Tight Buffer Indoor Cable 8F G50 MMF ClearCurve® OM3 0.9mm TB3, Dca-s1a, d1, a1

The Corning logo consists of the word "CORNING" in a white, serif, all-caps font, centered within a solid blue square.

Corning Comunicacoes Opticas • Estrada do Camorim 633 • Jacarepagua CEP 22780-070 • Rio De Janeiro, RJ Brazil
+55 21 3416 5150 • FAX: +55 21 2441 2037 • www.corning.com/opcomm/csa

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.