

Everon® LAN1 Fiber Housing Front panel loaded with pigtails, LC Duplex, 96 Fibers, 1U, Multimode OM3/OM4, stackable splice bridge, black

CORNING

Part Number:
LAN1-96AD-BRDG-B

The LANscape® housing family was designed for various applications in 19-racks and main distribution frames. The fixed or sliding housings can be equipped with industry common adapter types in different fiber categories and are suitable for direct field termination, fusion splicing with pigtails as well as preterminated solutions. The four back openings accommodate cable glands. Additional brackets for cable strain relief for FTTH/FTTO applications or U-Clips for Plug & Play™ and EDGE™ trunks can be mounted at the backside.

The space-optimized interior makes it easy to work with ongoing moves, adds and changes (MACs), thus reducing the risk of network disruptions.

Features and Benefits

Easy to remove top cover

No tools needed

Housing made of aluminium

Lightweight, but robust

Quick-mount feature

Allows single-person mounting of housing

Accomodate different termination methods


Pigtail splicing, field connectorisation, preterminated cables, Plug& Play™ or EDGE™ trunks can be installed in the same housing

Low installation depth

Mountable in shallow cabinets or racks

Multiple labelling options

Port numbering above and below adapter modules or customised labels



Everon® LAN1 Fiber Housing Front panel loaded with pigtails, LC Duplex, 96 Fibers, 1U, Multimode OM3/OM4, stackable splice bridge, black

CORNING

Specifications

General Specifications

Fiber Category	50 µm MM (OM3/OM4)
Access Type	Front, top, rear
Lockable	No
Mounting Type	Rack 19-in

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Temperature Range, Installation	-10 °C to 60 °C (14 °F to 140 °F)
Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)
Temperature Range, Storage	-10 °C to 60 °C (14 °F to 140 °F)

Design

Fiber Count	96
Splice Tray Type	No Splice Trays
Housing Material	Aluminum
Additional cable number reachable with accessories	4
Maximum cable number in basic unit with accessories	4
Cable entry type	Prepunched circular
Number of pigtails	96
Number of Splice Trays	0
Pigtail Length	2 m
Adapter Color Front	Aqua
Adapter Type Front	LC PC duplex shuttered
Splice Protectors Type	Heat Shrink

Everon® LAN1 Fiber Housing Front panel loaded with pigtails, LC Duplex, 96 Fibers, 1U, Multimode OM3/OM4, stackable splice bridge, black

CORNING

Design

Number of Adapters	48
Number of Splice Protectors	0
Total splice capacity	96 universal splices

Design - Adapter

Housing Color	Black
Keyed adapter	No
Shuttered adapter	Yes
Adapter Type	LC PC duplex shuttered

Specifications - Connector A

Polish	PC
Insertion Loss, Max.	0.25 dB

Specifications - Connector B

Polish	PC
--------	----

Dimensions

Height	44 mm
Width	483 mm
Depth	233 mm

Ordering Information

Product Number	LAN1-96AD-BRDG-B
Package Contents	LANscape Fiber Housing with adapters, stackable splice organizers for heat-shrink splice protectors including colored pigtails, 1x M20 cable gland and basic accessories

Everon® LAN1 Fiber Housing Front panel loaded with pigtails, LC Duplex, 96 Fibers, 1U, Multimode OM3/OM4, stackable splice bridge, black



Ordering Information	
Height Unit	1 U
Units per Delivery	1/1
Shipping Height	55 mm
Shipping Width	532 mm
Shipping Depth	350 mm



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.