

LC Duplex to LC Duplex Patch cord, 2 F, Zipcord Tight-Buffered Cable, LSZH, 2.0 mm legs SMF-28® Ultra single-mode (OS2), 2 m



CORNING

Part Number:
040402G5Z20002M

Patch cords are used for non-permanent connections between patch panels, transmission equipment, etc. Pre-assembled cables allow for the implementation of complete Plug & Play solutions. When such a solution is adopted with accurate dimensioning and appropriate cable routing, it is possible to install even large cabling systems rapidly.

Features and Benefits

Connectors

LC Duplex connector according to TIA/EIA-604 -10 - All connectors are tested to FOTP -21. - Connectors are pre-radius polished to provide the optimal end-face geometry for long-term performance

Cable

- Low smoke (IEC 61034) and zero-halogen (LSZH), flame retardant to IEC 60332-3-24 (C) and noncorrosive to IEC 60754-2 (FRNC)
- Cables are metal free; hence, there are no ground-loop or potential-equalization problems. Completely dry design (without gel).
- Color of outer sheath: OM1, OM2 – orange; OM3, OM4 – aqua; OS2 – yellow

LC Duplex to LC Duplex Patch cord, 2 F, Zipcord Tight-Buffered Cable, LSZH, 2.0 mm legs SMF-28® Ultra single-mode (OS2), 2 m

CORNING

Specifications

General Specifications

Flame Rating	LSZH/FRNC
Fiber Category	SMF-28® Ultra 242 Optical Fiber
Cable Assembly Type	Two Fiber
Cable Type	Tight-Buffered

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Intermateability	Compliant with TIA/EIA-604-10

Environmental Conditions

Temperature Range, Installation	-5 °C to 50 °C (23 °F to 122 °F)
Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)
Temperature Range, Storage	-10 °C to 60 °C (14 °F to 140 °F)

Design

Fiber Count	2
Outer Jacket Material	LSZH/FRNC
Outer Jacket Color	Yellow

Mechanical Specifications

Minimum Bend Radius	10 mm
Tensile Strength	300 N
Nominal Outer Diameter	4 mm
Crush Resistance	1000 N/10 cm

LC Duplex to LC Duplex Patch cord, 2 F, Zipcord Tight-Buffered Cable, LSZH, 2.0 mm legs SMF-28® Ultra single-mode (OS2), 2 m

CORNING

Specifications - Connector A

Reflectance, Typical	≤ -58 dB
Polish	UPC
Insertion Loss, Typical	0.1 dB
Insertion Loss, Max.	0.3 dB
Tensile Strength Jacketed Cable	44 N
Durability	≤ 0.2 dB change, 500 rematings, FOTP-21
Keyed (security)	No
Boot Color	Blue / White
Connector Type	LC Duplex
Ferrule Material	Ceramic
Housing Color	Blue
Housing Material	Composite
Boot Type	Individual

Specifications - Connector B

Reflectance, Typical	≤ -58 dB
Polish	UPC
Insertion Loss, Typical	0.1 dB
Insertion Loss, Max.	0.3 dB
Tensile Strength Jacketed Cable	44 N
Durability	≤ 0.2 dB change, 500 rematings, FOTP-21
Keyed (security)	No
Boot Color	Blue / White
Connector Type	LC Duplex
Ferrule Material	Ceramic
Housing Color	Blue
Boot Type	Individual

**LC Duplex to LC Duplex Patch cord, 2 F, Zipcord
Tight-Buffered Cable, LSZH, 2.0 mm legs SMF-28®
Ultra single-mode (OS2), 2 m**

CORNING

Dimensions

Length	2 m
Outer Diameter	2 mm
Weight	0.02 kg

Ordering Information

Product Number	040402G5Z20002M
EAN Code	4042673601142
Packaging Method	Cardboard box
Units per Delivery	1/1
Shipping Height	180 mm
Shipping Width	250 mm
Shipping Depth	380 mm



Corning Comunicacoes Opticas • Estrada do Camorim 633 • Jacarepagua CEP 22780-070 • Rio De Janeiro, RJ Brazil
+55 21 3416 5150 • FAX: +55 21 2441 2037 • www.corning.com/opcomm/csa

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.