


# FutureCom™ U/FTP 250/23, black Category 6, 1000 m



**Part Number:  
CCXERA-B0047-C001-L7**

The FutureCom™ U/FTP 250 AWG23 cable is designed for applications up to 250 MHz and its transmission characteristics exceed Category 6 specifications according to EN 50288-5-1, IEC 61156-5 and TIA/EIA 568. High system margins for the complete link according to ISO/IEC 11801Ed.2.2 (2011) and EN 50173 (Series) will be achieved by using corresponding hardware together with this copper data cable. Due to the very low delay skew between the pairs these FutureCom cables are especially suitable for Gigabit Ethernet. The cable has a streamlined construction and low weight. Each pair is individually foil shielded, which guarantees outstanding shielding characteristics. The cable satisfies Class B interference radiation standards according to EN 55022, as well as immunity according to EN 55024, which enables the realization of CE-compatible networks.

## Features and Benefits

Flame retardant according to IEC 60332-3-24 and EN 50266-2-4 (FR), EN 13501-6, non-corrosive according to IEC 60754-2 (NC) and EN 50267

---

Supports Power over Ethernet (PoE / PoE+ / PoE++) according IEEE 802.3bt



# FutureCom™ U/FTP 250/23, black Category 6, 1000 m



## Specifications

General Specifications	
Environment	Indoor
Category	6
Bandwidth	250 MHz
Halogen-free	Yes
Area/Range of Application	Dry and damp rooms
Reaction to fire	Dca - s2, d1, a1
Cable Type	U/FTP

Cable Design	
Conductor	Copper Wire, AWG 23
Conductor Insulation	Halogen-free foam-skin material
Outer Jacket Material	LSZH™/FRNC
Outer Jacket Color	Black

Mechanical Specifications	
Fire Load	0.49 MJ/m
Nominal Outer Diameter	6.9 mm
Min. Bend Radius Installation	8x Cable-Ø
Maximum Tensile Strength	100 N

Electrical Characteristics	
Conductor resistance unbalance	1 %
Delay skew	4 ns/100 m
Max. loop resistance	170 Ω/km
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max

# FutureCom™ U/FTP 250/23, black Category 6, 1000 m



## Electrical Characteristics

Coupling Attenuation	60 dB
Insulation Resistance	5000 MΩ*km
Surface transfer impedance	100 mΩ

## Ordering Information

Packing Type	Drum
--------------	------

## Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Flame Test Method	Reaction to fire according to EN 13501-6


## Environmental Conditions

Temperature Range, Installation	0 °C to 50 °C
Temperature Range, Operation	-20 °C to 60 °C

## Electrical Characteristics

Frequency [MHz]	1	4	10	100	250
Attenuation according to Standard [db/100m]	2.1	3.8	6.0	19.9	33.0
Typical attenuation [db/100m]	2.0	3.6	5.5	17.9	28.9
NEXT according to Standard [db/100m]	66.0		59.3	44.3	38.3
Typical NEXT Values [db/100m]	100.0	100.0	100.0	94.0	89.0
ACR-N according to Standard [db/100m]	63.9		53.3	24.4	5.3
Typical ACR-N Values [db/100m]	98.0	96.4	94.5	76.1	60.1

# FutureCom™ U/FTP 250/23, black Category 6, 1000 m



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2020 Corning Optical Communications. All rights reserved.