

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 E9 SMF-28e+® ITU G652.D CT 3.0



Part Number:
006EEU-13122A2G

The central tube cable construction, by isolating the fibres from installations and environmental rigors, provides stable and highly reliable transmission parameters. The fibres in are color coded for quick, easy identification.

The cable construction, based on a central buffer tube, is very compact, light and flexible, and ideal for connections requiring a moderate fiber count.

These cables are designed for installation in conduits, ducts and in-house.

Features and Benefits

All-dielectric cable construction

Requires no grounding or bonding

Laminated swelling glass yarns

Improved rodent resistance and longitudinal water protection

UV- and microbe-resistant

Can be installed in ducts or conduits

Small diameter and bend radius

Easy installation in space-constrained areas

Fibres colour coding to Telcordia-Bellcore

Easy identification of the individual fibres

Waterblocking technology


OSP (outdoor) applications

Silicon-free outer jacket

The cable jacket is free of harmful to paint structures

Flame retardant

LSZH™/FRNC



Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 E9 SMF-28e+®
ITU G652.D CT 3.0, Dca,s2,d2,a1

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 E9 SMF-28e+® ITU G652.D CT 3.0



Specifications


General Specifications	
Environment	Indoor/Outdoor
Cable type	Single Tube
Product type	Dielectric armour
Fibre category	Single-mode (OS2)
Flame rating	LSZH™/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)BH
Application	Duct, Vertical Riser, General Purpose Horizontal

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Flame Test Method	Flame retardant according to IEC 60332-1-2 (single cable), Reaction to fire according to EN 50575 and EN 13501-6, Low smoke according to IEC 61034 and zero halogen to IEC 60754-1, Non-corrosive according to IEC 60754-2
Waterblocking	IEC 60794-1-2 F5
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable)
Reaction to fire requirements	Reaction to fire according to EN 50575 and EN 13501-6
Smoke density	Low Smoke to IEC 61034
Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Standards	
Fibre Standards	TIA/EIA-492CAAB, IEC 60793-2-50 Type B1.3, ITU-T G.652.D, ISO/IEC 11801 Ed.2.2

Environmental Conditions	
Temperature range, installation	-5 °C to 50 °C

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 E9 SMF-28e+® ITU G652.D CT 3.0



Environmental Conditions

Temperature range, storage	-25 °C to 70 °C
Temperature range, operation	-20 °C to 60 °C

Cable Design

Cable marking	Metre - Handset - CE 17 EN 50575 Dca,s2,d2,a1 - Sine - CORNING - Fiber Optic Cable - Year - U-DQ(ZN)BH 6 E9 CT 3.0 LSZH(TM)/FRNC
Fibre count	6
Number of ripcords	1
Outer jacket colour	Black
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer jacket nominal thickness	1.2 mm
Tensile strength elements and/or armouring - Layer 1	Laminated swelling glass yarn armour
Buffer tube diameter	3 mm
Fibre colouring	Blue, orange, green, brown, grey, white


Mechanical Specifications

Crush resistance	1500 N/10 cm
Fire load	0.94 MJ/m
Max. tensile strength for installation	1000 N
Min. bend radius installation	130 mm
Min. bend radius operation	100 mm
Nominal outer diameter	6.6 mm

Optical Characteristics

Cable cutoff wavelength	1260 nm
Fibre code	E

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 E9 SMF-28e+® ITU G652.D CT 3.0



Optical Characteristics	
Fibre name	E9/125 SMF28e+®
Fibre Type	Single-mode
Fibre core diameter	8.2 µm
Maximum Attenuation	0.36 dB/km / 0.36 dB/km / 0.22 dB/km
Serial 1 gigabit ethernet	5000 MHz*km / - / -
Serial 10 gigabit ethernet	10000 MHz*km / - / 40000 MHz*km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fibre category	OS2

Ordering Information	
Product Number	006EEU-13122A2G
EAN Code	4056418100760
Maximum delivery length	6000 m
Weight	46 kg/km



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.