

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 G62.5 MMF InfiniCor® OM1 CT 3.0



Part Number:
006KEU-13108A2G

The central tube cable construction, by isolating the fibres from installations and environmental rigors, provides stable and highly reliable transmission parameters. The fibres in are color coded for quick, easy identification.

The cable construction, based on a central buffer tube, is very compact, light and flexible, and ideal for connections requiring a moderate fiber count.

These cables are designed for installation in conduits, ducts and in-house.

Features and Benefits

All-dielectric cable construction

Requires no grounding or bonding

Laminated swelling glass yarns

Improved rodent resistance and longitudinal water protection

UV- and microbe-resistant

Can be installed in ducts or conduits

Small diameter and bend radius

Easy installation in space-constrained areas

Fibres colour coding to Telcordia-Bellcore

Easy identification of the individual fibres

Waterblocking technology

OSP (outdoor) applications

Silicon-free outer jacket

The cable jacket is free of harmful to paint structures

Flame retardant

LSZH™/FRNC



Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 G62.5 MMF
InfiniCor® OM1 CT 3.0, Dca,s2,d2,a1

Specifications

General Specifications	
Environment	Indoor/Outdoor
Cable type	Single Tube
Product type	Dielectric armour
Fibre category	62.5 µm MM (OM1)
Flame rating	LSZH™/FRNC

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 G62.5 MMF InfiniCor® OM1 CT 3.0




Cable Design	
Cable marking	Metre - Handset - CE 17 EN 50575 Dca,s2,d2,a1 - Sine - CORNING - Fiber Optic Cable - Year - U-DQ(ZN)BH 6 OM1 CT 3.0 LSZH(TM)/FRNC
Fibre count	6
Number of ripcords	1
Outer jacket colour	Black
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer jacket nominal thickness	1.2 mm
Tensile strength elements and/or armouring - Layer 1	Laminated swelling glass yarn armour
Buffer tube diameter	3 mm
Fibre colouring	Blue, orange, green, brown, grey, white

Mechanical Specifications	
Crush resistance	1500 N/10 cm
Fire load	0.94 MJ/m
Max. tensile strength for installation	1000 N
Min. bend radius installation	130 mm
Min. bend radius operation	100 mm
Nominal outer diameter	6.6 mm

Optical Characteristics	
Fibre code	K
Fibre name	G62.5L/125 InfiniCor® 300
Fibre Type	Multimode
Fibre core diameter	62.5 µm
Minimum effective modal bandwidth (EMB)	220 MHz*km / -
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Min. overfilled launch (OFL) bandwidth	200 MHz*km / 600 MHz*km

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x6 G62.5 MMF InfiniCor® OM1 CT 3.0



Optical Characteristics

Serial 1 gigabit ethernet	300 MHz*km / 550 MHz*km
Serial 10 gigabit ethernet	33 MHz*km / -
Typical attenuation	2.9 dB/km / 0.7 dB/km
Wavelengths	850 nm / 1300 nm
Fibre category	OM1

Ordering Information

Product Number	006KEU-13108A2G
EAN Code	4056418100692
Maximum delivery length	4000 m
Weight	46 kg/km



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.