


FutureCom™ E250 Unshielded OCK6U8, E250U, RJ45 Vol, Cat6, Bag/8, White



Part Number:
FQ100031258

#A> C-@.6 /; <<1> 5: @1>/; ; : 1/@ <>; OA/@? C; >7
 @; 31@41>@; <>; B501 -; 1-?E-@; -A?1 ?; 8A@; ; 2; >
 O1<8; E5: 3 4534-?<110 /; ; : 1/@; ; ? @4>; A34; A@ -
 . A5805: 3. (41 &J45 6-/7 5? - 71E /; 9<; ; 1: @5: @45?
 ?E?@19. (41 6-/7K? A: 5=A1 @C; /-. 81 1: @>E <; 5: @?
 418< 9-71 5: ?@-88-@; ; ?59<81. (41 @>-O5@; ; -8
 ; : 1-/85/7 O1?53: 1: -. 81? -; 1-?E, @; ; 8-81??
 @1>95: -@; ; ; A: ?4518O10 @C5?@10 <-5> /-. 81?,
 911@; 3 5: OA?@>E <1>2; >9-: /1 ?@-: 0->0?.

F1-@A>1? -: 0 B1: 10@?

Tool-less jack

E-?E -: 0 =A5/7 @; 5: ?@-88 ->185-. 81 /; ; : 1/@; ;
 (41 /; ; OA/@; >? ->1 C5>10 5: - ?5: 381 ; <1>-@; ;

Two cable entry points

1?? /-. 81 . 1: O5: 3 >1=A5>10 - . 1@@1> /; 9<85-: /1
 C5@4 95: 59A9 . 1: 0 >-O5A?
 E: -. 81? - C501 >-: 31 ; 2 /-. 81 >; A@; 3 ; <@; ; ?
 E-?E @; A?1 5: @534@ ?<-/1?

Reusable

J-/7 /-: . 1 >1A?10 1B1: -2@1> C5>5: 3 95?@-71

No untwisting of pairs before termination

! 5: 595F10 ?@5<<5: 3 81: 3@4 - 8595@10 <-5> A: @C5?@ -
 <-5>? 71<@@ @; 31@41>; ; ; C5>1 3A501 >1=A5>10

Clip-in mounting

D1?53: 10 @; 0@ 9-: E ; @41> -//1??; >51?

Accepts solid and stranded conductors


E: -. 81? L6-/7-@; -<8A3M /-. 81? @; . 1 9-: A2-/@A>10
 A?5: 3 ?@-: O10 /; ; OA/@; >?

Integral shutter

" ; -005@; ; -8 ?4A@@1>5: 3 >1=A5>10 ; : 2-/1<8-@1?



FutureCom™ E250 Unshielded OCK6U8, E250U, RJ45 Vol, Cat6, Bag/8, White



' <1/50/-@; : ?

Design	
H; A?5: 3 9-@1>5-8	\$8-?@5/
C; 8; A>	* 45@1
C; : 0A/@; >	26 - 22 A* G
J-/7 (E<1	&J45 - 8/8
I: ?A8-@5; : 05-91@1> 9-D.	1.6 99
" A9. 1> ; 2 ' @-: 010 * 5>1?	7


Mechanical Specifications	
C; : @-/@ ?A2-/1	G; 80, 1.6 J9
&1<> ; 0A/5. 585@E	' 1B1>-8 @591? >1A?- . 81
' ; 850 * 5>1 D5-91@1>	0.5 99 @; 0.65 99
' @-: 010 * 5>1 D5-91@1>	0.15 99 @; 0.2 99

General Specifications	
C-@13; >E	6

Dimensions	
1: 3@4	34 99
H1534@	23 99
* 50@4	18 99

Ordering Information	
\$-/7-35: 3 91@4; 0	B-3 ; 2 8 / 1 B; D
\$-/75: 3 * 1534@	1.24 73
) : 5@? <1> 0185B1>E	96/1

FutureCom™ E250 Unshielded OCK6U8, E250U, RJ45 Vol, Cat6, Bag/8, White



Environmental Conditions	
(19<1>-@A>1 >: 31, ; <1>-@5; :	-10 IC @; 60 IC (14 IF @; 140 IF)



C; >: 5: 3 #<@5/-8 C; 99A: 5/-@5; : ? G9. H & C; . KG N 18<F531> ' @>-??1 121 N 10117 B1>@5: , G1>9-: E
+00 800 2675 4641 N FA+: +49 30 5303 2335 N [CCC./; >: 5: 3./; 9/; </; 99/191-](#)

A /; 9<@1@1 @5?@5: 3 ; 2 @41 @>-019->?? ; 2 C; >: 5: 3 #<@5/-8 C; 99A: 5/-@5; : ? 5? -B-@8-. @1 -@ CCC./; >: 5: 3./; 9/; </; 99/191-/@>-019->??.
C; >: 5: 3 #<@5/-8 C; 99A: 5/-@5; : ? 5? I' # 9001 -: 0 I' # 14001 /1>@5010. H 2020 C; >: 5: 3 #<@5/-8 C; 99A: 5/-@5; : ?. A@>534@? >1?1>B10.