

# ALTOS® Loose Tube Dielectric Armour Outdoor Cable LT 2.3 8x12 E9 SMF-28e+® ITU G652.D



**Part Number:**  
**096ERG-T3122A20**

Corning glass-yarn armored loose tube cables are designed for outdoor use for campus, city and intercity backbones in duct installations.

The loose tube cable construction, by isolating the fibers from installations and environmental rigors, provides stable and highly reliable transmission parameters. The buffer tubes and fibers in each tube are color coded for quick and easy identification.

The SZ-stranded construction further reduces installation and environmental influences on the transmission parameters and allows mid-span access.

These cables are designed for installation in conduits and ducts.

## Features and Benefits

### **Waterblocking technology**

Outside Plant (OSP) applications

### **All-dielectric cable construction**

Requires no grounding or bonding

### **UV and microbe resistant**

Can be installed in ducts

### **Dry cable core by means of water-swellable tape and elements**

Allows efficient and craft-friendly cable preparation in outdoor or indoor/outdoor applications

### **Laminated glass yarns**

For improved rodent resistance

### **Fibres/buffer tubes colour coded to Telcordia-Bellcore**

Easy identification of the individual tubes and fibres

### **SZ-stranded, loose tube design**

Isolates fibres from installation and environmental rigors and facilitates mid-span access



# ALTOS® Loose Tube Dielectric Armour Outdoor Cable LT 2.3 8x12 E9 SMF-28e+® ITU G652.D



## Specifications

General Specifications	
Environment	Outdoor
Cable type	Loose tube
Product type	Dielectric armour
Fibre category	Single-mode (OS2)
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	A-DQ(ZN)B2Y
Application	Duct

Standards	
Fibre Standards	TIA/EIA-492CAAB, IEC 60793-2-50 Type B1.3, ITU-T G.652.D, ISO/IEC 11801 Ed.2.2

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-2 F5

Environmental Conditions	
Temperature range, installation	-5 °C to 50 °C
Temperature range, operation	-30 °C to 70 °C
Temperature range, storage	-40 °C to 70 °C

Cable Design	
Cable marking	Meter - Handset - Sine - CORNING - Year -ALTOS (R) A-DQ(ZN)B2Y 8X12 E9 LT 2.3
Central element	Dielectric with Polyethylene coating
Fibre count	96
Buffer tube colour coding	Blue, orange, green, brown, grey, white, red, black

# ALTOS® Loose Tube Dielectric Armour Outdoor Cable LT 2.3 8x12 E9 SMF-28e+® ITU G652.D



Cable Design	
Number of ripcords	1
Outer jacket colour	Black
Outer jacket material	Linear Low Density Polyethylene (LLDPE)
Outer jacket nominal thickness	1.5 mm
Tensile strength elements and/or armouring - Layer 1	Laminated glass yarn armour
Buffer tube colour	Blue, orange, green, brown, grey, white, red, black
Buffer tube diameter	2.25 mm
Central element diameter	3.9 mm
Number of active tubes	8
Number of tube positions	8
Tape	Water-swellable
Fibre colouring	Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink, turquoise
Fibres per tube	12

Mechanical Specifications	
Crush resistance	2000 N/10 cm
Min. bend radius installation	245 mm
Min. bend radius operation	185 mm
Nominal outer diameter	12.1 mm

Optical Characteristics	
Cable cutoff wavelength	1260 nm
Fibre code	E
Fibre name	E9/125 SMF28e+®
Fibre Type	Single-mode
Fibre core diameter	8.2 µm
Maximum Attenuation	0.36 dB/km / 0.36 dB/km / 0.22 dB/km

# ALTOS® Loose Tube Dielectric Armour Outdoor Cable LT 2.3 8x12 E9 SMF-28e+® ITU G652.D



## Optical Characteristics

Serial 1 gigabit ethernet	5000 MHz*km / - / -
Serial 10 gigabit ethernet	10000 MHz*km / - / 40000 MHz*km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fibre category	OS2

## Ordering Information

Product Number	096ERG-T3122A20
EAN Code	4042673558804
Weight	116 kg/km



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.