

The LANscape® housing family was designed for various applications in 19-in racks and main distribution frames. The fixed or sliding housings can be equipped with industry common adapter types in different fiber categories and are suitable for direct field termination, fusion splicing with pigtails as well as preterminated solutions. The four back openings accommodate cable glands. Additional brackets for cable strain relief for FTTD/FTTO applications or U-Clips for Plug & Play™ and EDGE™ trunks can be mounted at the backside. The space-optimized interior makes it easy to work with ongoing moves, adds and changes (MACs), thus reducing the risk of network disruptions.

Features and Benefits

No tools needed

Lightweight, but robust


Allows single-person mounting of housing

Pigtail splicing, field connectorisation, preterminated cables, Plug & Play™ or EDGE™ trunks can be installed in the same housing

Mountable in shallow cabinets or racks

Port numbering above and below adapter modules or customised labels

Additional protection at no extra cost



LANscape® Fiber Housing, loaded with LC Duplex shuttered adapters and pigtails, 48 Fibers, 1U, Multimode OM3/OM4, universal splice pack, protectors not included, black



Specifications

Housing Color	Aqua
Shuttered adapter	Yes
Adapter Type	LC duplex shuttered

Fiber Count	48
Splice Tray Type	Universal cassette with organisers for heat-shrink and crimp splice protectors
Housing Material	Aluminum
Additional cable number reachable with accessories	4
Maximum cable number in basic unit with accessories	4
Cable entry type	Prepunched circular
Number of pigtails	48
Number of Splice Trays	4
Pigtail Length	2 m
Splice Protectors Type	Without Organizer and Protectors
Number of Adapters	24
Number of Splice Protectors	0
Total splice capacity	48 universal splices

Fiber Category	50 µm MM (OM3/OM4)
Access Type	Front, top, rear
Lockable	Yes
Mounting Type	Rack 19-in



Fiber Count	48

Height	44 mm
Width	483 mm
Depth	233 mm

Product Number	LAN1-48AD-PGTL-B
Package Contents	LANscape Fiber Housing with adapters, splice packs including colored pigtails, 1x M20 cable gland and basic accessories
Units per Delivery	1/1

Height	44 mm
Width	483 mm
Depth	233 mm



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.