

# FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

grey, 6 m

CORNING

The application-neutral FutureCom™ category 6<sub>A</sub> patch cords have four individual foil-shielded pairs (PiMF) and an additional braid shield (S/FTP). They are assembled with a shielded RJ45 connectors on each end. The zero halogen patch cords (LSZH) are non-corrosive according to IEC 60754-2 (FRNC) and EN 50267, low smoke according to IEC 61034 and EN 50268 and flame retardant according to IEC 60332-1, Category B and EN 50266-2-1. FutureCom™ S500 patch cords provide additional latch protection.

They are available in various lengths and colours.

## Features

S/FTP flex cable, Category 7

Application-neutral due to using all four pairs of RJ45 connectors

Minimum surface transfer impedance of cable

Outstanding transmission characteristics according to 10GBase-T

Additional latch protection

Category 6<sub>A</sub>

PVP Certificate



## Specifications

### General Specifications

Cable Assembly Type	Patch Cords
Environment	Indoor
Cable Type	S/FTP
Halogen-free	Yes
Category	6 <sub>A</sub>

### Temperature Range

Operation	-20 °C to 60 °C
-----------	-----------------

# FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

grey, 6 m

CORNING

## Design - Connector A

Connector Type	RJ45 - 8/8
----------------	------------

## Mechanical Specifications - Connector A

Durability	750 Cycles
------------	------------

## Electrical Specifications - Connector

Insulation Resistance	
-----------------------	--

## Design - Connector B

Copper Connector Type - B	RJ45 - 8/8
---------------------------	------------

## Mechanical Specifications - Connector B

Durability	750 Cycles
------------	------------

## Cable Design

Min. Bend Radius Installation	40 mm
Min. Bend Radius Operation	30 mm
Outer diameter	5.8 mm
Outer Jacket Material	LSZH™/FRNC
Outer Jacket Colour	grey

## Mechanical Characteristics

Conductor insulation	Braided shield Individual pair shield (PiMF)
----------------------	----------------------------------------------

## Electrical characteristics (at 20°C)

Max. loop resistance	
DC resistance unbalance	2 %
Impedance $Z_0$ at 0-100 MHz	
Impedance $Z_0$ at 101-250 MHz	

# FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

grey, 6 m



## Electrical characteristics (at 20°C)

Impedance $z_0$ at 251-600 MHz	
Surface transfer impedance	
Mutual capacity	43 pF/m
Earth coupling at 0.001 MHz	1600
	4.3 ns/m
Delay skew	20 ns/100 m

## Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	-----------------------------------------------------------

## Ordering Information

Part Number	CCAAGB-G1002-A060-C0
Product Description	FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector, grey, 6 m
EAN Code	4042673499947
Weight	0.288 kg
Length	6 m

## Shipping Information

Units per Delivery	1/1
--------------------	-----



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2014 Corning Optical Communications. All rights reserved.