

The application-neutral FutureCom™ category 6_A patch cords have four individual foil-shielded pairs (PiMF) and an additional braid shield (S/FTP). They are assembled with a shielded RJ45 connectors on each end. The zero halogen patch cords (LSZH) are non-corrosive according to IEC 60754-2 (FRNC) and EN 50267, low smoke according to IEC 61034 and EN 50268 and flame retardant according to IEC 60332-1, Category B and EN 50266-2-1. FutureCom™ S500 patch cords provide additional latch protection.

They are available in various lengths and colours.

Features

- S/FTP flex cable, Category 7
- Application-neutral due to using all four pairs of RJ45 connectors
- Minimum surface transfer impedance of cable (<10 mΩ/m at 10 MHz)
- Outstanding transmission characteristics according to 10GBase-T
- Additional latch protection
- Category 6_A
- PVP Certificate

Specifications

Cable assembly type	Patch Cords
Environment	Indoor
Cable type	S/FTP
Halogen-free	Yes
Category	6 _A

Operation	-20 °C to 60 °C
-----------	-----------------



Part Number: CCAAGB-G1002-A200-C0

Connector type	RJ45 - 8/8
----------------	------------

Durability	750 Cycles
------------	------------

Insulation Resistance	$\geq 5000 \text{ M}\Omega$
-----------------------	-----------------------------

Connector type	RJ45 - 8/8
----------------	------------

Durability	750 Cycles
------------	------------

Min. Bend Radius Installation	47 mm
-------------------------------	-------

Min. Bend Radius Operation	18 mm
----------------------------	-------

Outer diameter	5.8 mm
----------------	--------

Outer jacket material	LSZH™/FRNC
-----------------------	------------

Outer jacket colour	Grey
---------------------	------

Conductor Insulation	Braided shield Individual pair shield (PiMF)
----------------------	--

Max. loop resistance	290 Ω /km
----------------------	------------------

DC resistance unbalance	2 %
-------------------------	-----

Impedance Z_0 at 0-100 MHz	100 Ω +- 15%
------------------------------	---------------------

Impedance Z_0 at 101-250 MHz	100 Ω +- 18%
--------------------------------	---------------------

Impedance z_0 at 251-600 MHz	100 Ω +/- 25%
Surface transfer impedance	< 10 m Ω /m per meter at 10 MHz
Mutual capacity	43 pF/m
Earth coupling at 0.001 MHz	1600
Propagation delay \geq 10 MHz	4.3 ns/m
Delay skew	20 ns/100 m

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Ordering Information

Part Number	CCAAGB-G1002-A200-C0
Product Description	FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector, grey, 20 m
EAN Code	4042673522294
Weight	0.96 kg
Length	20 m

Shipping Information

Units Per Delivery	1/1
--------------------	-----



A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified.
© 2017 Corning Optical Communications. All rights reserved.