



Part Number: 012TEU-13188D2G



# FREEDM™ Gel-Free Central Tube Indoor/ Outdoor Cable

12F G50 MMF ClearCurve® OM3 CT 3.0

CORNING

## Specifications

General Specifications	
Environment	Indoor / Outdoor
Application	Direct Buried, Duct, Vertical Riser, General Purpose Horizontal
Cable type	Central Tube
Product type	Dielectric armour
Flame rating	LSZH™/FRNC
Fibre category	50 µm MM (OM3)
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-BQ(ZN)BH
Previous part number	012TSZ-T2B80D20
Previous coding following DIN VDE 0888-3	A-BQ(BN)H

Temperature Range	
Installation and Assembly	-5 °C to 50 °C
Operation	-30 °C to 70 °C
Storage	-30 °C to 70 °C

Cable design	
Fibre count	12
Fibre colouring	Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink, turquoise
Buffer tube diameter	3.0 mm
Buffer tube colour	green
Tensile Strength Elements and/or Armouring - Layer 1	Laminated glass yarn armour
Number of Ripcords	1
Outer jacket material	Flame-retardant, non-corrosive / low-smoke, zero-halogen (FRNC / LSZH) material
Outer jacket colour	black
Outer Jacket Nominal Thickness	1.2 mm
Cable Marking	Meter Handset Sine CORNING Fibre Optic Cable Year FREEDM™ U-BQ(ZN)BH 12 OM3CC CT 3.0 LSZH™/FRNC

# FREEDM™ Gel-Free Central Tube Indoor/ Outdoor Cable

12F G50 MMF ClearCurve® OM3 CT 3.0

CORNING

## Mechanical Characteristics Cable

Nominal Outer Diameter	7.0 mm
Weight	48 kg/km
Min. Bend Radius Installation	140 mm
Min. Bend Radius Operation	110 mm
Max. Tensile Strength for Installation	1000 N
Crush Resistance (reversible)	1400 N/10 cm
Fire Load	0.83 MJ/m

## Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

## Fibre Specifications

### Optical Characteristics (cabled)

Fibre Name	G50/125 ULTRA-BEND 7.5
Fibre Core Diameter	50 µm
Fibre category	OM3
Fibre Code	T
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Typical Attenuation	2.4 dB/km / 0.8 dB/km
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	300 m / 333 m
Min. Overfilled Launch (OFL) Bandwidth	1500 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	2000 MHz*km / -
Induced attenuation @ 7.5 mm radius	< 0.2 dB / -

- Notes:
- 1) 50 µm multimode fibre macrobend loss  $\leq 0.2$  dB at 850 nm for two turns around 7.5 mm radius mandrel
  - 2) Meets 0.75 ns optical skew when used in all Corning Plug and Play™/Pretium EDGE® systems solutions.
  - 3) Improved attenuation and bandwidth options available
  - 4) Bend-insensitive single-mode fibres available on request
  - 5) Contact a Corning Customer Care Representative for additional information

# FREEDM™ Gel-Free Central Tube Indoor/ Outdoor Cable

12F G50 MMF ClearCurve® OM3 CT 3.0



## Ordering Information

Part Number	012TEU-13188D2G
Product Description	FREEDM™ Gel-Free Central Tube Indoor/Outdoor Cable 12F G50 MMF ClearCurve® OM3 CT 3.0
EAN Code	4042673561569

## Shipping Information

Maximum delivery length	4,000 m
-------------------------	---------



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2015 Corning Optical Communications. All rights reserved.