




Part Number: 004TEY-13138A2G Cross Section of Order Number: 0



Central Tube Steel Armour Indoor/Outdoor Cable

4F G50 MMF ClearCurve® OM2 CT 3.0



Specifications

General Specifications	
Environment	Indoor / Outdoor
Application	Direct Buried, Duct, Vertical Riser, General Purpose Horizontal
Cable Type	Loose Tube
Product Type	Corrugated steel armour
Flame Rating	LSZH™/FRNC
Fibre category	50 µm MM (OM2)
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)(SR)H
Previous Part Number	FWCT01-S0004-G004
Previous coding following DIN VDE 0888-3	A-DQ(ZN)(SR)H

Temperature Range	
Installation and Assembly	-5 °C to 50 °C
Operation	-20 °C to 60 °C
Storage	-25 °C to 70 °C

Cable Design	
Fibre Count	4
Fibre colouring	Blue, orange, green, brown
Buffer tube colour	green
Buffer tube diameter	3 mm
Number of Ripcords	2
Tensile Strength Elements and/or Armouring - Layer 1	Corrugated steel tape armour with dielectric strength elements (aramid yarns) and swellable elements
Outer Jacket Material	Flame-retardant, non-corrosive / low-smoke, zero-halogen (FRNC / LSZH) material
Outer Jacket Colour	black
Outer Jacket Nominal Thickness	1.5 mm
Cable Marking	Meter Handset Sine CORNING Fibre Optic Cable Year U-DQ(ZN)(SR)H 4 OM2CC CT 3.0 LSZH™/FRNC

Central Tube Steel Armour Indoor/Outdoor Cable

4F G50 MMF ClearCurve® OM2 CT 3.0

CORNING

Mechanical Characteristics Cable

Nominal Outer Diameter	7.5 mm
Weight	76 kg/km
Min. Bend Radius Installation	150 mm
Min. Bend Radius Operation	110 mm
Max. Tensile Strength for Installation	1000 N
Crush Resistance (reversible)	2000 N/10 cm
Fire Load	1.16 MJ/m

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Fibre Specifications

Optical Characteristics (cabled)

Fibre Name	G50/125 ULTRA-BEND 7.5
Fibre Core Diameter	50 µm
Fibre category	OM2
Fibre Code	T
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Typical attenuation	2.4 dB/km / 0.8 dB/km
Serial 1 Gigabit Ethernet	750 m / 600 m
Serial 10 Gigabit Ethernet	150 m / -
Min. Overfilled Launch (OFL) Bandwidth	700 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	950 MHz*km / -
Induced attenuation @ 7.5 mm radius	< 0.2 dB / -

- Notes:
- 1) 50 µm multimode fibre macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel
 - 2) Improved attenuation and bandwidth options available
 - 3) Bend-insensitive single-mode fibres available on request
 - 4) Contact a Corning Customer Care Representative for additional information

Central Tube Steel Armour Indoor/Outdoor Cable

4F G50 MMF ClearCurve® OM2 CT 3.0



Ordering Information

Part Number	004TEY-13138A2G
Product Description	Central Tube Steel Armour Indoor/Outdoor Cable 4F G50 MMF ClearCurve® OM2 CT 3.0
EAN Code	4042673580553

Shipping Information

Maximum Delivery Length	4,000 m
-------------------------	---------



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2014 Corning Optical Communications. All rights reserved.